

# ELECTROMECHANICAL ROTARY ACTUATORS

## GUN/TURRET/RADAR DRIVES FOR LAND SYSTEMS



Moog's electromechanical rotary actuators are designed to meet or exceed the demanding requirements of new and existing land system gun, turret, and radar applications through world-class stabilization and pointing accuracy. These actuators are used for new and existing combat vehicle platform control applications, heavy payloads requiring high slew-to-cue capability, and as a power drive unit for larger mechanical actuated systems.

Features include a brushless DC motor which can be integrated in a 28VDC system up to a 600VDC system. The output pinion of the actuator can pair with a ring or sector gear or can couple directly to the load. The gear can be modified to mate with any customer defined ring/sector gear. The actuator also features a failsafe clutch, manual drive, and no-back.

Moog is a worldwide designer, manufacturer, and integrator of custom precision motion control and stabilization systems for the defense industry. Our electromechanical rotary and linear actuators are ideal for new systems, upgrades to older hydraulic systems, and for sustainment services.

### KEY FEATURES

- Brushless DC motor (28VDC to 600VDC options)
- Integrated brushless resolver or absolute encoder for motor commutation
- Output pinion designed to interface with customer defined ring/sector gear
- Integrated failsafe 18VDC to 32VDC clutch
- Integrated manual drive with custom input ratios
- No-back (optional)
- Design, tested, and qualified to MIL-STD 810E and MIL-STD 461E
- MIL-Spec electrical connectors
- On board absolute encoder position sensor (optional)
- Oil filled for lubrication and heat management (optional)



# PLATFORM AZIMUTH DRIVE


CA76728

## PERFORMANCE

Features	Specifications
Peak torque	267.5 FTLB (403.4 Nm)
Rated torque	136 FTLB (184.4 Nm)
Rated speed	164.2 rpm
No load speed	217 rpm
Minimum static holding torque (brake engaged)	997.6 FTLB (1,353 Nm)
Supply voltage (nom.)	600VDC
Backlash	< 28 arc-min.
Weight	84 lbs (185 kg)



## ARCHITECTURAL AND DIMENSIONAL DRAWING



# LAUNCHER AZIMUTH DRIVE


ICD CCB91028

## PERFORMANCE

Features	Specifications
Peak torque	3,975 FTLB (5,389 Nm)
Rated torque	1,553 FTLB (2,106 Nm)
Rated speed	19 rpm
No load speed	75 rpm
Minimum static holding force (clutch engaged)	2,310 FTLB (3,132 Nm)
Supply voltage (nom.)	600VDC
Backlash	< 3 arc-min.
Weight	360 lbs (792 kg)



## ARCHITECTURAL AND DIMENSIONAL DRAWING




# INFANTRY FIGHTING VEHICLE ELEVATION ACTUATOR

C7L265M

## PERFORMANCE


Features	Specifications
Peak force	4,260 LBF (19.0 kN)
Rated force	1,450 LBF (6.45 kN)
Rated speed	4.3"/s (109 mm/s)
No load speed	5.4"/s (137 mm/s)
Clutch holding force	9,000 LBF (40.0 kN)
Supply voltage	18VDC - 32VDC, 270VDC, 650VDC; 3 x 380VAC, 50 - 60 Hz
Stiffness	300 kLBF/in (52.5 kN/mm)
Backlash	0.015" (0.381 mm)
Weight	76.7 lbs (34.7 kg)
Retracted length	22.9" (581 mm)
Extended length	33.3" (846 mm)




# INFANTRY FIGHTING VEHICLE TRAVERSE ACTUATOR

## PERFORMANCE

Features	Specifications
Peak torque	280 Nm (2,480 LBIN)
Rated torque	85 Nm (750 LBIN)
Rated speed	85 rpm
Clutch holding torque	400 Nm (3,570 LBIN)
Supply voltage	24VDC, 48VDC, 270VDC, or 650VDC
Stiffness	7.75 kNm/deg (68.6 kLBIN/deg)
Backlash	5.7 arc-min.
Weight	54 lbs (24.5 kg)




## ARCHITECTURAL AND DIMENSIONAL DRAWING



# PLATFORM POWER DRIVE UNIT


ICD CB60333



## PERFORMANCE

Features	Specifications
Peak torque	254 FTLB (344.4 Nm)
Rated torque	56.7 FTLB (76.9 Nm)
Rated speed	103 rpm
No load speed	143 rpm
Minimum static holding torque (brake engaged)	219 FTLB (297 Nm)
Supply voltage (nom.)	600VDC
Weight	30.9 lbs (67.9 kg)

## ARCHITECTURAL AND DIMENSIONAL DRAWING



**MOOG**  
SPACE AND DEFENSE GROUP

### AMERICAS

defense@moog.com  
moog.com/defense

### EUROPE

defenceurope@moog.com  
moog.com/defence

### AUSTRALIA

info.australia@moog.com  
moog.com.au



Moog Space and Defense



@MoogSDG



@MoogSDG



@MoogSDG

The appearance of U.S. Department of Defense (DoD) visual information does not imply or constitute DoD endorsement.

Equipment described herein falls under the jurisdiction of the ITAR and requires US Government Authorization for export purposes. Diversion contrary to US law is prohibited.

©2023 Moog, Inc. All rights reserved.

Product and company names listed are trademarks or trade names of their respective companies.